

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

MESCLA

TECHNICAL CHARACTERISTICS

| | | | |
|---|------------------------|---------------------------|------------|
| Available Formats: | 12x24 | | |
| Style Description: | Marble | Glaze Application Method: | Inkjet |
| Visual Characteristics: | Marble | Number of Faces/Screens: | 19 |
| Thickness in mm: | 8.5 MM | Number of Punches/Molds: | |
| Modular Suitability: | Yes | Body Type: | Porcelain |
| Application: | Residential/Commercial | Color Body Unglazed: | Glazed |
| Recycled Content: Post or Pre Customer | | Surface Type: | Matte/Flat |
| Rectified: | Pressed | Recommended Grout Joint: | 3 MM |

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

| | | | |
|------------------------------|--------|---|--------------|
| Water Absorption: | 0.33 | Static COF: | |
| Shade Variation (1, 2, 3, 4) | V3 | Dynamic COF: | 0.42 |
| Scratch Hardness (MOHS) | 6 | Breaking Strength: | 1894.1 |
| Frost Resistant: | Yes | Thermal Shock Resistance: | Not Declared |
| PEI/Abrasion Resistance: | 3 | Deep Abrasion Test <175mm ² : | |
| Chemical Resistance: | GA/GLB | | |

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".