

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME

**PRISMA ONYX**

## TECHNICAL CHARACTERISTICS

Available Formats:	12x24, 24x24, 3x3 Mosaic 12x12 Sheet, 3x24 Bullnose		
Style Description:	Onyx	Glaze Application Method:	Inkjet
Visual Characteristics:	Onyx	Number of Faces/Screens:	30 (12x24), 14 (24x24)
Thickness in mm:	8.25 (12x24)	Number of Punches/Molds:	
Modular Suitability:		Body Type:	Porcelain
Application:	Residential	Color Body Unglazed:	Only Glazed
Recycled Content: Post or Pre Customer		Surface Type:	Matte/Polished
Rectified or Pressed	Rectified	Recommended Grout Joint:	

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	<0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	.48 Wet
Scratch Hardness (MOHS)		Breaking Strength:	1897.8 N
Frost Resistant:	Yes	Thermal Shock Resistance:	Fully Resistant
PEI/Abrasion Resistance:	3	Deep Abrasion Test <175mm <sup>2</sup> :	
Chemical Resistance:	Class 4		

*ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.*