## **NEW PRODUCT SERIES**

Technical Information Spec-sheet



## International Wholesale Tile, LLC

ARMANI

TECHNICAL CHARACTERISTICS				
Available Formats:	12x24 & 24x24			
Style Description:	Marble	Glaze Application Method:	Inkjet	
Visual Characteristics:	Marble	Number of Faces/Screens:	24x24: 10, 12x24: 20	
Thickness in mm:	9 MM	Number of Punches/Molds:		
Modular Suitability:	Yes	Body Type:	Porcelain	
Application:	Residential/Commercial	Color Body Unglazed:	Glazed	
Recycled Content:		Surface Type:	Matte/Polished	
Post or Pre Customer				
Rectified or Pressed	Rectified	Recommended Grout Joint:	Yes	

## PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<0.05%	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	Polished: 0.37, Matte: 0.41
Scratch Hardness (MOHS)	Class 3 in Polish and Class	Breaking Strength:	<1300 N
	6 > in Matt		
Frost Resistant:	Yes	Thermal Shock Resistance:	YES
PEI/Abrasion Resistance:	4	Deep Abrasion Test	YES
		<175mm <sup>2</sup> :	
Chemical Resistance:	Yes		

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.