

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

Classic

TECHNICAL CHARACTERISTICS

Available Formats:	2x8, 4x12, 4x16, 3x12 Picket, 3x6, 8x16, .5x8 Quarter Round		
Style Description:	Subway	Glaze Application Method:	Waterfall Process
Visual Characteristics:	Subway	Number of Faces/Screens:	
Thickness in mm:	2x8= 7.5mm All others= 7.8mm	Number of Punches/Molds:	
Modular Suitability:		Body Type:	Ceramic
Application:	Residential Wall/Shower	Color Body Unglazed:	Normal
Recycled Content: Post or Pre Customer	7% before consumption	Surface Type:	Glossy or matte
Rectified or Pressed	Pressed	Recommended Grout Joint:	

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	14%-18%	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	
Scratch Hardness (MOHS)	5	Breaking Strength:	0.57 kN
Frost Resistant:	No	Thermal Shock Resistance:	Yes
PEI/Abrasion Resistance:	2	Deep Abrasion Test <175mm ² :	
Chemical Resistance:	CLASS A		

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.