

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

Classic

TECHNICAL CHARACTERISTICS

Available Formats:	2x8, 4x12, 4x16, 3x12 Picket, Bullnose, .5x8 Quarter Round		
Style Description:	Subway	Glaze Application Method:	Waterfall Process
Visual Characteristics:	Subway	Number of Faces/Screens:	
Thickness in mm:	2x8= 7.5mm All others= 7.8mm	Number of Punches/Molds:	
Modular Suitability:		Body Type:	Ceramic
Application:	Residential Wall/Shower	Color Body Unglazed:	Normal
Recycled Content: Post or Pre Customer	7% before consumption	Surface Type:	Glossy or matte
Rectified or Pressed	Pressed	Recommended Grout Joint:	

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	14%-18%	Static COF:	
Shade Variation (1, 2, 3, 4)	V1	Dynamic COF:	
Scratch Hardness (MOHS)	5	Breaking Strength:	0.57 kN
Frost Resistant:	No	Thermal Shock Resistance:	Yes
PEI/Abrasion Resistance:	2	Deep Abrasion Test <175mm ² :	
Chemical Resistance:	CLASS A		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".