

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME

**DOLOMITE**

## TECHNICAL CHARACTERISTICS

Available Formats:	12x24, 24x48		
Style Description:	Dolomite	Glaze Application Method:	Inkjet
Visual Characteristics:	Dolomite	Number of Faces/Screens:	64 (12x24), 16 (24x48)
Thickness in mm:	9.5 and 10.5	Number of Punches/Molds:	
Modular Suitability:	No	Body Type:	Porcelain
Application:	Residential	Color Body Unglazed:	Glazed Porcelain
Recycled Content: Post or Pre Customer		Surface Type:	Glossy/Polished/Flat
Rectified:	Rectified	Recommended Grout Joint:	Minimum 2 MM

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	>0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	0.22
Scratch Hardness (MOHS)		Breaking Strength:	1600-2400 N
Frost Resistant:	Yes	Thermal Shock Resistance:	
PEI/Abrasion Resistance:	4	Deep Abrasion Test <175mm <sup>2</sup> :	No
Chemical Resistance:			

*ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.*