

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME

**FINLANDIA**

## TECHNICAL CHARACTERISTICS

Available Formats:	24x48		
Style Description:	Wood	Glaze Application Method:	Inkjet
Visual Characteristics:	Wood	Number of Faces/Screens:	6
Thickness in mm:	10 MM	Number of Punches/Molds:	1
Modular Suitability:	No	Body Type:	Gres Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	Uncolor Body
Recycled Content: Post or Pre Customer	RECYCLED CONTENT POST	Surface Type:	Matte
Rectified:	Yes	Recommended Grout Joint:	

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	0.5-3%	Static COF:	
Shade Variation (1, 2, 3, 4)	V4	Dynamic COF:	<0.4
Scratch Hardness (MOHS)	8	Breaking Strength:	
Frost Resistant:	Yes	Thermal Shock Resistance:	BLA
PEI/Abrasion Resistance:	4	Deep Abrasion Test <175mm <sup>2</sup> :	Yes
Chemical Resistance:	GLA		

*ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.*