

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME

**ICON**

## TECHNICAL CHARACTERISTICS

Available Formats:	12x36		
Style Description:	Décor Wall Tile	Glaze Application Method:	Inkjet
Visual Characteristics:		Number of Faces/Screens:	1
Thickness in mm:	10.5	Number of Punches/Molds:	1
Modular Suitability:	Residential Wall/Shower	Body Type:	Ceramic
Application:		Color Body Unglazed:	
Recycled Content: Post or Pre Customer		Surface Type:	Matte
Rectified or Pressed		Recommended Grout Joint:	2mm

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	>10%	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	No
Scratch Hardness (MOHS)		Breaking Strength:	600-900N
Frost Resistant:	No	Thermal Shock Resistance:	Resists
PEI/Abrasion Resistance:		Deep Abrasion Test <175mm <sup>2</sup> :	No
Chemical Resistance:	Complies with Iso 10545-13		

### Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".