

# NEW PRODUCT SERIES

Technical Information Spec-sheet



## International Wholesale Tile, LLC

SERIES NAME

**LAPIETRA**

### TECHNICAL CHARACTERISTICS

Available Formats:	24x24 Polished/Matte		
Style Description:	Stone	Glaze Application Method:	Inkjet
Visual Characteristics:	Onyx	Number of Faces/Screens:	12
Thickness in mm:	8.5 MM	Number of Punches/Molds:	1
Modular Suitability:	Yes	Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	
Recycled Content: Post or Pre Customer	0%	Surface Type:	Glossy/Polished/Matte
Rectified or Pressed	Rectified	Recommended Grout Joint:	2mm- 3mm

### PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:		Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	>0.40
Scratch Hardness (MOHS)		Breaking Strength:	
Frost Resistant:	Yes	Thermal Shock Resistance:	
PEI/Abrasion Resistance:	4	Deep Abrasion Test <175mm <sup>2</sup> :	
Chemical Resistance:			

#### Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".