

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME

**MARMOR**

## TECHNICAL CHARACTERISTICS

Available Formats:	24x24		
Style Description:	Marble	Glaze Application Method:	Standard Screen
Visual Characteristics:	Marble	Number of Faces/Screens:	4
Thickness in mm:	7.7 mm	Number of Punches/Molds:	Flat Mold (1 Punch)
Modular Suitability:	No	Body Type:	Ceramic
Application:	Residential	Color Body Unglazed:	Unglazed
Recycled Content: Post or Pre Customer	No	Surface Type:	Matte
Rectified or Pressed	Rectified	Recommended Grout Joint:	5mm

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	Ceramic 6-8%	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	0.4
Scratch Hardness (MOHS)	Min 5	Breaking Strength:	MIN 1350 N
Frost Resistant:	No	Thermal Shock Resistance:	Resistant
PEI/Abrasion Resistance:	4	Deep Abrasion Test <175mm <sup>2</sup> :	Yes
Chemical Resistance:	<b>NO DAMAGE FROM CHEMICAL - RESISTANT</b>		

### Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".