

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

MERRICK

TECHNICAL CHARACTERISTICS

Available Formats:	6x36		
Style Description:	Wood	Glaze Application Method:	
Visual Characteristics:	Wood	Number of Faces/Screens:	6
Thickness in mm:	8.5- 9 MM approx.	Number of Punches/Molds:	
Modular Suitability:	No	Body Type:	Gres Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	Normal
Recycled Content: Post or Pre Customer		Surface Type:	Satin
Rectified or Pressed	Pressed	Recommended Grout Joint:	

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	2.50%	Static COF:	
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	R9
Scratch Hardness (MOHS)		Breaking Strength:	UNI ENI ISO 10545-4
Frost Resistant:	Yes	Thermal Shock Resistance:	UNI EN ISO 10545-9
PEI/Abrasion Resistance:	4	Deep Abrasion Test <175mm ² :	
Chemical Resistance:	CLASSE UB min		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".