NEW PRODUCT SERIES

Technical Information Spec-sheet



SERIES NAME

OCEAN STONES SLICED

TECHNICAL CHARACTERISTICS				
Available Formats:	11.75X12			
Style Description:	Decorative Stone	Glaze Application Method:		
Visual Characteristics:	Stone	Number of Faces/Screens:		
Thickness in mm:	10	Number of Punches/Molds:		
Modular Suitability:		Body Type:	Stone	
Application:	Residential & Wet Floor	Color Body Unglazed:		
Recycled Content:		Surface Type:	Flat	
Post or Pre Customer				
Rectified or Pressed		Recommended Grout Joint:		

PRODUCT TESTING INFORMATION					
Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)					
Water Absorption:		Static COF:			
Shade Variation (1, 2, 3, 4)		Dynamic COF:			
Scratch Hardness (MOHS)		Breaking Strength:			
Frost Resistant:	No	Thermal Shock Resistance:			
PEI/Abrasion Resistance:		Deep Abrasion Test			
		<175mm ² :			
Chemical Resistance:					

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".