

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME

**SLICED BASKETWEAVE**

## TECHNICAL CHARACTERISTICS

Available Formats:	12x12		
Style Description:	Decorative Stone	Glaze Application Method:	
Visual Characteristics:	Stone	Number of Faces/Screens:	
Thickness in mm:	10	Number of Punches/Molds:	
Modular Suitability:		Body Type:	Stone
Application:	Residential & Wet Floor	Color Body Unglazed:	
Recycled Content: Post or Pre Customer		Surface Type:	Flat/Polished
Rectified or Pressed		Recommended Grout Joint:	

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:		Static COF:	
Shade Variation (1, 2, 3, 4)		Dynamic COF:	
Scratch Hardness (MOHS)		Breaking Strength:	
Frost Resistant:	No	Thermal Shock Resistance:	
PEI/Abrasion Resistance:		Deep Abrasion Test <175mm <sup>2</sup> :	
Chemical Resistance:			

*ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.*