

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

Super

TECHNICAL CHARACTERISTICS

Available Formats:	12x24 Matte		
Style Description:	White	Glaze Application Method:	Inkjet
Visual Characteristics:	White	Number of Faces/Screens:	1
Thickness in mm:	8.5 MM	Number of Punches/Molds:	1
Modular Suitability:	Yes	Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	Glazed Porcelain
Recycled Content: Post or Pre Customer	0%	Surface Type:	Matte
Rectified or Pressed	Rectified	Recommended Grout Joint:	2mm- 3mm

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<0.50%	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	.70
Scratch Hardness (MOHS)	5	Breaking Strength:	2023.21 N
Frost Resistant:	Yes	Thermal Shock Resistance:	Fully resistance
PEI/Abrasion Resistance:	4	Deep Abrasion Test <175mm ² :	
Chemical Resistance:			

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

Super

TECHNICAL CHARACTERISTICS

Available Formats:	12x24 Polished		
Style Description:	White	Glaze Application Method:	Inkjet
Visual Characteristics:	Polished	Number of Faces/Screens:	1
Thickness in mm:	8.5 MM	Number of Punches/Molds:	1
Modular Suitability:	Yes	Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	Glazed Porcelain
Recycled Content: Post or Pre Customer	0%	Surface Type:	Polished
Rectified or Pressed	Rectified	Recommended Grout Joint:	2mm- 3mm

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<0.50%	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	
Scratch Hardness (MOHS)		Breaking Strength:	2023.21 N
Frost Resistant:	Yes	Thermal Shock Resistance:	Fully resistance
PEI/Abrasion Resistance:	3	Deep Abrasion Test <175mm ² :	
Chemical Resistance:			

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

Super

TECHNICAL CHARACTERISTICS

Available Formats:	24x24 Matte		
Style Description:	White	Glaze Application Method:	Inkjet
Visual Characteristics:	White	Number of Faces/Screens:	1
Thickness in mm:	8.5 MM	Number of Punches/Molds:	1
Modular Suitability:	Yes	Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	Glazed Porcelain
Recycled Content: Post or Pre Customer	0%	Surface Type:	Matte
Rectified or Pressed	Rectified	Recommended Grout Joint:	2mm- 3mm

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<0.50%	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	.70
Scratch Hardness (MOHS)		Breaking Strength:	2023.21 N
Frost Resistant:	Yes	Thermal Shock Resistance:	Fully resistance
PEI/Abrasion Resistance:	4	Deep Abrasion Test <175mm ² :	
Chemical Resistance:			

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

Super

TECHNICAL CHARACTERISTICS

Available Formats:	24x24 Polished		
Style Description:	White	Glaze Application Method:	Inkjet
Visual Characteristics:	Polished	Number of Faces/Screens:	1
Thickness in mm:	8.5 MM	Number of Punches/Molds:	1
Modular Suitability:	Yes	Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	Glazed Porcelain
Recycled Content: Post or Pre Customer	0%	Surface Type:	Polished
Rectified or Pressed	Rectified	Recommended Grout Joint:	2mm- 3mm

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<0.50%	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	
Scratch Hardness (MOHS)		Breaking Strength:	2023.21 N
Frost Resistant:	Yes	Thermal Shock Resistance:	Fully resistance
PEI/Abrasion Resistance:	3	Deep Abrasion Test <175mm ² :	
Chemical Resistance:			

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

Super

TECHNICAL CHARACTERISTICS

Available Formats:	24x48 Matte		
Style Description:	White	Glaze Application Method:	Inkjet
Visual Characteristics:	White	Number of Faces/Screens:	1
Thickness in mm:	8.5 MM	Number of Punches/Molds:	1
Modular Suitability:	Yes	Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	Glazed Porcelain
Recycled Content: Post or Pre Customer	0%	Surface Type:	Matte
Rectified or Pressed	Rectified	Recommended Grout Joint:	2mm- 3mm

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<0.50%	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	.70
Scratch Hardness (MOHS)		Breaking Strength:	2023.21 N
Frost Resistant:	Yes	Thermal Shock Resistance:	Fully resistance
PEI/Abrasion Resistance:	4	Deep Abrasion Test <175mm ² :	
Chemical Resistance:			

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

Super

TECHNICAL CHARACTERISTICS

Available Formats:	24x48 Polished		
Style Description:	White	Glaze Application Method:	Inkjet
Visual Characteristics:	White	Number of Faces/Screens:	1
Thickness in mm:	8.5 MM	Number of Punches/Molds:	1
Modular Suitability:	Yes	Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	Glazed Porcelain
Recycled Content: Post or Pre Customer	0%	Surface Type:	Matte
Rectified or Pressed	Rectified	Recommended Grout Joint:	2mm- 3mm

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<0.50%	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	
Scratch Hardness (MOHS)		Breaking Strength:	2023.21 N
Frost Resistant:	Yes	Thermal Shock Resistance:	Fully resistance
PEI/Abrasion Resistance:	3	Deep Abrasion Test <175mm ² :	
Chemical Resistance:			

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.