

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

TIMELESS

TECHNICAL CHARACTERISTICS

Available Formats:	24x24 Polished		
Style Description:	Contemporary	Glaze Application Method:	Standard
Visual Characteristics:	Contemporary	Number of Faces/Screens:	10
Thickness in mm:	8 mm	Number of Punches/Molds:	One (Glossy only, No Punch or Texture)
Modular Suitability:	No	Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	Unglazed
Recycled Content: Post or Pre Customer	No	Surface Type:	Polished
Rectified or Pressed	Rectified	Recommended Grout Joint:	3 MM to 5MM

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	
Scratch Hardness (MOHS)	Min 5	Breaking Strength:	Min 1350 N
Frost Resistant:	Yes	Thermal Shock Resistance:	Resistant
PEI/Abrasion Resistance:	4	Deep Abrasion Test <175mm ² :	Yes
Chemical Resistance:	Resistant		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".