

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

TURIN

TECHNICAL CHARACTERISTICS

Available Formats:	12x24		
Style Description:	Travertino	Glaze Application Method:	Inkjet
Visual Characteristics:	Marble	Number of Faces/Screens:	12
Thickness in mm:	7.4	Number of Punches/Molds:	1
Modular Suitability:	No	Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	Glazed
Recycled Content: Post or Pre Customer	9%	Surface Type:	Matte
Rectified or Pressed	Pressed	Recommended Grout Joint:	3-5 MM

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	Eb<0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	Dry: 0.79 Wet: 0.54
Scratch Hardness (MOHS)	>=5	Breaking Strength:	>700N
Frost Resistant:	Yes	Thermal Shock Resistance:	
PEI/Abrasion Resistance:	4	Deep Abrasion Test <175mm ² :	No
Chemical Resistance:	>=B		

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.