

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

Asha Onice

TECHNICAL CHARACTERISTICS

Available Formats:	12x24, 24x24, 24x48		
Style Description:	Onyx	Glaze Application Method:	Inkjet
Visual Characteristics:	Onyx	Number of Faces/Screens:	12x24: 8, 24x24: 6, 24x48:4
Thickness in mm:	9 mm	Number of Punches/Molds:	1
Modular Suitability:	No	Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	No
Recycled Content: Post or Pre Customer		Surface Type:	Glossy/Polished/Flat
Rectified or Pressed	Rectified	Recommended Grout Joint:	3/16"

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	0.05%	Static COF:	
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	
Scratch Hardness (MOHS)		Breaking Strength:	
Frost Resistant:	Yes	Thermal Shock Resistance:	
PEI/Abrasion Resistance:	4	Deep Abrasion Test <175mm ² :	No
Chemical Resistance:			

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.