

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

Glassalike

TECHNICAL CHARACTERISTICS

Available Formats:	12x24, 4x12		
Style Description:		Glaze Application Method:	H.D.I.T. Inkjet
Visual Characteristics:	Glass Block & Fluted	Number of Faces/Screens:	30
Thickness in mm:	10 mm	Number of Punches/Molds:	Block: 6, Fluted and Groove: 1
Modular Suitability:	No	Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	
Recycled Content: Post or Pre Customer	16%	Surface Type:	Matte/Glossy/Polished/Textured
Rectified or Pressed	Pressed	Recommended Grout Joint:	3-4.5 mm

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	-0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V4	Dynamic COF:	Matte: 0.51; Glossy: 0.18
Scratch Hardness (MOHS)	Glossy- 5; Matte- 6	Breaking Strength:	>35 N/mm ²
Frost Resistant:	Yes	Thermal Shock Resistance:	Resists
PEI/Abrasion Resistance:	Glossy: PEI 2 (Blu & Nero), PEI 3 (Grigio), 4 (Bianco, Taupe, Azzurro, Rosa & Lime). Matte: PEI 3 (Nero), PEI 4 (Bianco, Taupe & Grigio)	Deep Abrasion Test <175mm ² :	
Chemical Resistance:	A, LA, HA		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".