

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME

POESIA

## TECHNICAL CHARACTERISTICS

Available Formats:	24x24, 12x24, 2x2 Mosaic 12x12 Sheet, 3x24 Bullnose		
Style Description:	Limestone	Glaze Application Method:	HDIT Inkjet
Visual Characteristics:	Cement Stone Mix	Number of Faces/Screens:	24x24: 30, 12x24: 50
Thickness in mm:	9.5mm	Number of Punches/Molds:	1
Modular Suitability:	Yes	Body Type:	Porcelain (< .5%)
Application:	Residential/Commercial	Color Body Unglazed:	Yes
Recycled Content: Post or Pre Customer	15%	Surface Type:	Satin/Flat
Rectified:	Yes	Recommended Grout Joint:	No less than 1/8"

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	< .5%	Static COF:	N/A
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	0.74
Scratch Hardness (MOHS)	N/A	Breaking Strength:	1200N
Frost Resistant:	Yes	Thermal Shock Resistance:	Yes
PEI/Abrasion Resistance:	V	Deep Abrasion Test <175mm <sup>2</sup> :	Yes
Chemical Resistance:	10545-13-14		

### Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".