

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME

**PAVIA TRK**

## TECHNICAL CHARACTERISTICS

Available Formats:	6x36		
Style Description:	Wood Plank	Glaze Application Method:	Inkjet
Visual Characteristics:	Wood Plank	Number of Faces/Screens:	8
Thickness in mm:	10mm	Number of Punches/Molds:	1
Modular Suitability:	No	Body Type:	Ceramic
Application:	Residential	Color Body Unglazed:	Red Glazed
Recycled Content: Post or Pre Customer	N/A	Surface Type:	Matte/Textured
Rectified or Pressed	Pressed	Recommended Grout Joint:	3mm

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	6-10%	Static COF:	
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	≤0,4
Scratch Hardness (MOHS)	5	Breaking Strength:	800 N
Frost Resistant:	No	Thermal Shock Resistance:	No
PEI/Abrasion Resistance:	3	Deep Abrasion Test <175mm <sup>2</sup> :	No
Chemical Resistance:	GB / GLB		

### Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".