

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

BUTEO

TECHNICAL CHARACTERISTICS

Available Formats:	5x16 and 3x12		
Style Description:	Wall Tile	Glaze Application Method:	Standard Screen
Visual Characteristics:	Fume or "Subway"	Number of Faces/Screens:	1
Thickness in mm:	8 MM	Number of Punches/Molds:	1
Modular Suitability:		Body Type:	Ceramic
Application:	Residential/Shower	Color Body Unglazed:	
Recycled Content: Post or Pre Customer	3%	Surface Type:	Glossy/Matte
Rectified or Pressed	Pressed	Recommended Grout Joint:	3 MM

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	19%	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	No
Scratch Hardness (MOHS)		Breaking Strength:	Pass
Frost Resistant:	No	Thermal Shock Resistance:	
PEI/Abrasion Resistance:		Deep Abrasion Test <175mm ² :	No
Chemical Resistance:	Pass		

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.