

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

OASIS

TECHNICAL CHARACTERISTICS

Available Formats:	24x24, 9.25x9.25 Hex, 11.75x12 Intreccio Mosaic		
Style Description:	Wood	Glaze Application Method:	Inkjet
Visual Characteristics:	Wood	Number of Faces/Screens:	12 faces 24x24 and 10x11 Hexagon
Thickness in mm:	9.5 mm	Number of Punches/Molds:	1
Modular Suitability:	No	Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	Glazed
Recycled Content: Post or Pre Customer	10%	Surface Type:	Matte
Rectified or Pressed	Rectified	Recommended Grout Joint:	2mm

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	≤ 0.1%	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	wet > 0.42
Scratch Hardness (MOHS)	≥ 6	Breaking Strength:	S ≥ 1300N / R ≥ 35 N/mm ²
Frost Resistant:	Yes	Thermal Shock Resistance:	Resistant
PEI/Abrasion Resistance:	4	Deep Abrasion Test <175mm ² :	No
Chemical Resistance:	A - LA -HA		

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.