

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

NUSA

TECHNICAL CHARACTERISTICS

Available Formats:	8.25x9.75		
Style Description:	Marble	Glaze Application Method:	Inkjet
Visual Characteristics:	Marble	Number of Faces/Screens:	Plain White: 1, White Statuario 15
Thickness in mm:	8.5 MM	Number of Punches/Molds:	Plain Matte
Modular Suitability:	Yes	Body Type:	Porcelain
Application:	Residential/Commercial/ Exterior	Color Body Unglazed:	Normal Body Glazed
Recycled Content: Post or Pre Customer		Surface Type:	Matte
Rectified or Pressed	Pressed	Recommended Grout Joint:	Yes

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<0.05%	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	0.44 Wet, 0.69 Dry
Scratch Hardness (MOHS)	6	Breaking Strength:	43.08 N/mm ²
Frost Resistant:	Yes	Thermal Shock Resistance:	4.2x10 ⁻⁶ K-1
PEI/Abrasion Resistance:	4	Deep Abrasion Test <175mm ² :	
Chemical Resistance:	Class-AA		

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.