

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

ROVER

TECHNICAL CHARACTERISTICS

Available Formats:	8x48		
Style Description:	Wood Plank	Glaze Application Method:	Inkjet
Visual Characteristics:	Wood Plank	Number of Faces/Screens:	Beige & Bianco-10 Natural-9
Thickness in mm:	9 mm	Number of Punches/Molds:	1
Modular Suitability:	Yes	Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	Regular body with glazed surface
Recycled Content: Post or Pre Customer		Surface Type:	Matte
Rectified:	Yes	Recommended Grout Joint:	2mm

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<0.05%	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	<0.4
Scratch Hardness (MOHS)	Min 5	Breaking Strength:	Min. 2666N
Frost Resistant:	Yes	Thermal Shock Resistance:	No damage
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm ² :	Yes
Chemical Resistance:	No damage		

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacture. Use constitutes acceptance.