

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

TIRRENO TOSCANE

TECHNICAL CHARACTERISTICS

Available Formats:	12x24		
Style Description:	Rustic	Glaze Application Method:	Inkjet
Visual Characteristics:	Cement	Number of Faces/Screens:	24
Thickness in mm:	9.5 MM	Number of Punches/Molds:	
Modular Suitability:	Yes	Body Type:	Porcelain
Application:	Residential/Commercial/Exterior	Color Body Unglazed:	Normal
Recycled Content: Post or Pre Customer		Surface Type:	Glossy
Rectified:	Pressed	Recommended Grout Joint:	

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	≤ 0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	> .60
Scratch Hardness (MOHS)	8	Breaking Strength:	UNI ISO 10545-4
Frost Resistant:	Yes	Thermal Shock Resistance:	Resistant
PEI/Abrasion Resistance:	4	Deep Abrasion Test <175mm ² :	
Chemical Resistance:	CLASSE UB min		

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.