

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

FRATTO

TECHNICAL CHARACTERISTICS

Available Formats:	12x24, 24x24, 24x48, 3x3 Mosaic, 3x24 Bullnose		
Style Description:	Stone	Glaze Application Method:	Inkjet
Visual Characteristics:	Stone	Number of Faces/Screens:	24x48- 11, 24x24 -22, 12x24- 44
Thickness in mm:	8mm	Number of Punches/Molds:	
Modular Suitability:	Yes	Body Type:	Porcelain
Application:	Residential/Commercial/Exterior	Color Body Unglazed:	Color body Glazed
Recycled Content: Post or Pre Customer		Surface Type:	Matte/Flat
Rectified or Pressed	Rectified	Recommended Grout Joint:	3/16

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<0.1%	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	>0.42
Scratch Hardness (MOHS)	6	Breaking Strength:	2000 N
Frost Resistant:	Yes	Thermal Shock Resistance:	Resistant
PEI/Abrasion Resistance:	4,5 (Bianco)	Deep Abrasion Test <175mm ² :	No
Chemical Resistance:			

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.