

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

LINEA

TECHNICAL CHARACTERISTICS

Available Formats:	12x24		
Style Description:		Glaze Application Method:	
Visual Characteristics:	Modern Pattern	Number of Faces/Screens:	
Thickness in mm:		Number of Punches/Molds:	
Modular Suitability:		Body Type:	Ceramic
Application:	Residential/Commercial	Color Body Unglazed:	
Recycled Content: Post or Pre Customer		Surface Type:	Glossy/Matte
Rectified or Pressed	Rectified	Recommended Grout Joint:	

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	10% ≤E ≤16% - P4	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	
Scratch Hardness (MOHS)	4	Breaking Strength:	>230 >950
Frost Resistant:	Not Resistant	Thermal Shock Resistance:	
PEI/Abrasion Resistance:		Deep Abrasion Test <175mm ² :	Class 0
Chemical Resistance:	Class B		

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.