

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

BOW HEX

TECHNICAL CHARACTERISTICS

Available Formats:	8.5x9.75 Hex		
Style Description:	Matte hex with raised glaze	Glaze Application Method:	Digital Design Graphic Technology
Visual Characteristics:	Encaustic pattern with partial raised glaze	Number of Faces/Screens:	1
Thickness in mm:	10mm	Number of Punches/Molds:	
Modular Suitability:		Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	
Recycled Content: Post or Pre Customer		Surface Type:	Matte
Rectified or Pressed	Pressed	Recommended Grout Joint:	

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<0.5%	Static COF:	>.60
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	No
Scratch Hardness (MOHS)	6	Breaking Strength:	>1300 N
Frost Resistant:	Yes	Thermal Shock Resistance:	Resistant
PEI/Abrasion Resistance:	4	Deep Abrasion Test <175mm ² :	
Chemical Resistance:	Resistant		

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.