

NEW PRODUCT SERIES

Technical Information Spec-sheet



INTERNATIONAL WHOLESALE TILE, LLC

SERIES NAME

Dover

TECHNICAL CHARACTERISTICS

Available Formats:	10x60, 12x71	Glaze Application Method:	Inkjet
Style Description:	Wood look porcelain	Number of Faces/Screens:	12x71- 19
Thickness in mm:	9mm	Number of Punches/Molds:	1
Modular Suitability:	No	Body Type:	Porcelain
Application:	Residential <ul style="list-style-type: none"> Interior wall wet/dry Interior floor Exterior wall Commercial <ul style="list-style-type: none"> Interior wall wet/dry Interior floor Exterior wall 		
Rectified or Pressed:	Rectified	Color Body:	No
Recycled Content: Post or Pre Customer	N/A	Surface Type:	Matte
Country of Origin	Spain	Recommended Grout Joint:	2mm

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<.5%	Chemical Resistance:	GLA/GHA/GA
Shade Variation (1, 2, 3, 4)	2	Dynamic COF:	>.42
Scratch Hardness (MOHS)	6	Breaking Strength:	1600 - 2400N
Frost Resistant:	Yes	Thermal Shock Resistance:	Yes
PEI/Abrasion Resistance:	White- 4 Sand, Camel- 3	Deep Abrasion Test <175mm ² :	N/A

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacture. Use constitutes acceptance.