

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

DOVER

TECHNICAL CHARACTERISTICS

Available Formats:	10x60		
Style Description:	Wood	Glaze Application Method:	Inkjet
Visual Characteristics:	Wood	Number of Faces/Screens:	21
Thickness in mm:	10.5mm	Number of Punches/Molds:	1
Modular Suitability:	No	Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	UGL
Recycled Content: Post or Pre Customer	31%	Surface Type:	Matte
Rectified or Pressed	Rectified	Recommended Grout Joint:	2 MM

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	>0.42
Scratch Hardness (MOHS)	6	Breaking Strength:	1600 - 2400 N
Frost Resistant:	Yes	Thermal Shock Resistance:	Resists
PEI/Abrasion Resistance:		Deep Abrasion Test <175mm ² :	Yes
Chemical Resistance:	AMMONIUM CHLORIDE 100g/L: A HYDROCHLORIC ACID 3% & CITRIC ACID: COMPLIES WITH THE STANDARD		

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.