

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

KASBAH

TECHNICAL CHARACTERISTICS

Available Formats:	4.75x4.75 Base, 6.5x6.5 Star		
Style Description:	Solid Color	Glaze Application Method:	Inkjet
Visual Characteristics:	Solid Color	Number of Faces/Screens:	Base: 48
Thickness in mm:	8-9mm	Number of Punches/Molds:	Base: 2, Star: 2
Modular Suitability:	Yes	Body Type:	Porcelain
Application:	Residential/Commercial/Exterior	Color Body Unglazed:	
Recycled Content: Post or Pre Customer	51%	Surface Type:	Matte
Rectified or Pressed	Pressed	Recommended Grout Joint:	1/16

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	>0.42
Scratch Hardness (MOHS)	7	Breaking Strength:	>1300 N
Frost Resistant:	Yes	Thermal Shock Resistance:	Yes
PEI/Abrasion Resistance:	4	Deep Abrasion Test <175mm ² :	
Chemical Resistance:	Household Chemicals		

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.