



Luxwood XL Technical Specifications

Description: Luxury Engineered Vinyl Plank, Floating Floor with Attached EVA Pad

Warranty: Limited Lifetime Residential Wear Warranty
15 Year Limited Lt. Commercial Warranty

Installation: Unilin Click - Float, Glue Down

Construction: 6mm Stone Core Composite (Limestone + Virgin PVC)
with attached 2mm EVA Pad and 20 mil wear layer - total thickness 8mm

Size/Packing: Luxwood XL. - 9”x 60” x 8mm planks 6 pcs/box,
22.61 sf/box, 48 boxes / pallet, 1,085.28 sf/ pallet

Wear Finish: 2 layered Ceramic Bead, Aluminum Oxide Finish with Antimicrobial surface

TEST DATA

ASTM – E90-09 Airborne Sound Conduction:	STC 63 db
ASTM – E492-09 Impact Sound Conduction:	IIC 65 db / ΔIIC 21
ANSI A137.1 Dynamic Coefficient of Friction Test:	0.52 DCOF
ASTM F970-00 Static Load	1500 PSI (0.008 of an inch)
ASTM F 1515 Color Resistance to Light:	Meets <8.0 Δ E Requirement
ASTM F 1514 Color Resistance to Heat:	Meets <8.0 Δ E Requirement

