

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

MARROW

TECHNICAL CHARACTERISTICS

Available Formats:	3X12		
Style Description:	PICKET WALL TILE	Glaze Application Method:	STANDARD SCREEN
Rectified / Pressed:		Number of Faces/Screens:	1
Thickness in mm:	8 MM	Number of Punches/Molds:	1
Application:	RESIDENTIAL WALL	Body Type:	
Recycled Content: Post or Pre Customer	3%	Surface Type:	UNDULATED
		Recommended Grout Joint:	3 MM

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	19%	Dynamic COF:	N/A
Shade Variation (1, 2, 3, 4)	2	Breaking Strength:	PASS
Frost Resistant:	NO	Thermal Shock Resistance:	
PEI/Abrasion Resistance:	N/A	Chemical Resistance:	PASS

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacture. Use constitutes acceptance.