NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME	ALPS - ROCCIA - OCEAN WAVES
-------------	-----------------------------

TECHNICAL CHARACTERISTICS				
Available Formats:	6X24 & 6X6			
Style Description:	POOL TILES	Glaze Application Method:	INKJET	
Thickness in mm:	9.1 MM	Number of Faces/Screens:		
Application:	RESIDENTIAL, COMMERCIAL	Number of Punches/Molds:		
Rectified or Pressed:	RECTIFIED	Body Type:	PORCELAIN	
Recycled Content:		Surface Type:	GLOSSY	
Post or Pre Customer				
		Recommended Grout Joint:	2MM	

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	0.5	Chemical Resistance:	MIN CLASS GB / MIN CLASS AA
Shade Variation (1, 2, 3, 4)	1	Dynamic COF:	
Frost Resistant:	YES	Breaking Strength:	MIN 1300.0 N
PEI/Abrasion Resistance:	,	Thermal Shock Resistance:	YES

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacture. Use constitutes acceptance.