

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME

**LUCCA**

## TECHNICAL CHARACTERISTICS

|   |  |                           |   |
|---|--|---------------------------|---|
| Available Formats:                        | 24x48, 24x24, 12x24, Basketweave Mosaic, Hexagon Mosaic, 3x24 Bullnose |                           |   |
| Style Description:                        | MARBLE   | Glaze Application Method: | INKJET  |
| Thickness in mm:                          | 9  | Number of Faces/Screens:  | C.Marfil 24x48=5 24x24=10 12x24=20<br>Dolomite 24x48=4 24x24=8 12x24=16<br>Onyx 24x48=6 24x24=12 12x24=24<br>Volakis 24x48=4 24x24=8 12x24=16<br>Calacatta 24x48=6 24x24=8 12x24=12<br>Statuario 24x48=6 24x24=8 12x24=12 |
| Modular Suitability:                      | NO   | Number of Punches/Molds:  |   |
| Application:                              | RESIDENTIAL<br>COMMERCIAL  | Body Type:                | PORCELAIN   |
| Rectified or Pressed:                     | RECTIFIED  | Color Body:               |   |
| Recycled Content:<br>Post or Pre Customer |  | Surface Type:             | MATTE & POLISHED  |
|   |  | Recommended Grout Joint:  | 1/8"  |

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

|                              |   |   |         |
|------------------------------|---|---|---------|
| Water Absorption:            | <0.05%  | Chemical Resistance:                        | YES     |
| Shade Variation (1, 2, 3, 4) | 3   | Dynamic COF:                                | <0.42   |
| Scratch Hardness (MOHS)      | 3   | Breaking Strength:                          | <1300 N |
| Frost Resistant:             | YES   | Thermal Shock Resistance:                   |         |
| PEI/Abrasion Resistance:     | IV<br>III - Polished Calacatta &<br>Statuario colors only | Deep Abrasion Test<br><175mm <sup>2</sup> : | YES     |

*ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacture. Use constitutes acceptance.*