

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

LUCCA

TECHNICAL CHARACTERISTICS

Available Formats:	24x48, 24x24, 12x24, Basketweave Mosaic, Hexagon Mosaic, 3x24 Bullnose		
Style Description:	MARBLE	Glaze Application Method:	INKJET
Thickness in mm:	9	Number of Faces/Screens:	C.Marfil 24x48=5 24x24=10 12x24=20 Dolomite 24x48=4 24x24=8 12x24=16 Onyx 24x48=6 24x24=12 12x24=24 Volakis 24x48=4 24x24=8 12x24=16 Calacatta 24x48=6 24x24=8 12x24=12 Statuario 24x48=6 24x24=8 12x24=12
Modular Suitability:	NO	Number of Punches/Molds:	
Application:	RESIDENTIAL COMMERCIAL	Body Type:	PORCELAIN
Rectified or Pressed:	RECTIFIED	Color Body:	
Recycled Content: Post or Pre Customer		Surface Type:	MATTE & POLISHED
		Recommended Grout Joint:	1/8"

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<0.05%	Chemical Resistance:	YES
Shade Variation (1, 2, 3, 4)	3	Dynamic COF:	<0.42
Scratch Hardness (MOHS)	3	Breaking Strength:	<1300 N
Frost Resistant:	NO	Thermal Shock Resistance:	
PEI/Abrasion Resistance:	IV III - Polished Calacatta & Statuario colors only	Deep Abrasion Test <175mm ² :	YES

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacture. Use constitutes acceptance.