

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME

**MOTHER OF PEARL**

## TECHNICAL CHARACTERISTICS

Available Formats:	24x48, 12x24, 4x12, Basketweave Mosaic, Hexagon Mosaic, 3x3 Mosaic		
Style Description:	Mother of Pearl	Glaze Application Method:	INKJET
Thickness in mm:	8mm & 8.75mm		12x24 (24), 24x48 (6)
Modular Suitability:		Number of Punches/Molds:	
Application:	RESIDENTIAL COMMERCIAL	Body Type:	PORCELAIN
Rectified or Pressed:	RECTIFIED	Color Body:	
Recycled Content: Post or Pre Customer		Surface Type:	MATTE & POLISHED
		Recommended Grout Joint:	

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	<0.05%	Chemical Resistance:	YES
Shade Variation (1, 2, 3, 4)	3	Dynamic COF:	<0.42 (Matte only)
Scratch Hardness (MOHS)		Breaking Strength:	1897.78N
Frost Resistant:	YES	Thermal Shock Resistance:	
PEI/Abrasion Resistance:	III	Deep Abrasion Test <175mm <sup>2</sup> :	

*ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacture. Use constitutes acceptance.*