

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

MOTHER OF PEARL

TECHNICAL CHARACTERISTICS

| | | | |
|---|--|---------------------------|-----------------------|
| Available Formats: | 24x48, 12x24, Basketweave Mosaic, Hexagon Mosaic | | |
| Style Description: | Mother of Pearl | Glaze Application Method: | INKJET |
| Thickness in mm: | 8mm & 8.75mm | | 12x24 (24), 24x48 (6) |
| Modular Suitability: | | Number of Punches/Molds: | |
| Application: | RESIDENTIAL COMMERCIAL | Body Type: | PORCELAIN |
| Rectified or Pressed: | RECTIFIED | Color Body: | |
| Recycled Content: Post or Pre Customer | | Surface Type: | MATTE & POLISHED |
| | | Recommended Grout Joint: | |

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

| | | | |
|------------------------------|--------|---|--------------------|
| Water Absorption: | <0.05% | Chemical Resistance: | YES |
| Shade Variation (1, 2, 3, 4) | 3 | Dynamic COF: | <0.42 (Matte only) |
| Scratch Hardness (MOHS) | | Breaking Strength: | 1897.78N |
| Frost Resistant: | YES | Thermal Shock Resistance: | |
| PEI/Abrasion Resistance: | III | Deep Abrasion Test <175mm ² : | |

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacture. Use constitutes acceptance.