

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

Titanium

TECHNICAL CHARACTERISTICS

| | | | |
|---|---|---------------------------|------------------------------------|
| Available Formats: | 24x48, 24x24, 12x24, 3" Hexagon Mosaic, 3x24 Bullnose | | |
| Style Description: | Stone | Glaze Application Method: | Inkjet |
| Visual Characteristics: | Stone | Number of Faces/Screens: | 24x48 (7), 24x24 (14) , 12x24 (28) |
| x | 9 mm | Number of Punches/Molds: | |
| Modular Suitability: | No | Body Type: | Porcelain |
| Application: | Residential/Commercial/Exterior | Color Body Unglazed: | |
| Recycled Content: Post or Pre Customer | | Surface Type: | Matte/Textured |
| Rectified or Pressed | Rectified | Recommended Grout Joint: | Yes |

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

| | | | |
|------------------------------|--------|---|---------|
| Water Absorption: | <0.05% | Static COF: | |
| Shade Variation (1, 2, 3, 4) | 3 | Dynamic COF: | >0.42 |
| Scratch Hardness (MOHS) | 6 | Breaking Strength: | <1300 N |
| Frost Resistant: | No | Thermal Shock Resistance: | Yes |
| PEI/Abrasion Resistance: | 4 | Deep Abrasion Test <175mm ² : | Yes |
| Chemical Resistance: | Yes | | |

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.