

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

La Marca

TECHNICAL CHARACTERISTICS

Available Formats:	24x48, 32x32, 24x24, 12x24, 4x12, 6" Hex, 3" Hex, Picco Mosaic, 3x12 Bullnose		
Style Description:	Glazed Porcelain/Rectified	Glaze Application Method:	Ink Jet
Thickness in mm:		Number of Faces/Screens:	See below chart
Modular Suitability:	No	Number of Punches/Molds:	
Application:	Residential & Commercial	Body Type:	Porcelain
Rectified or Pressed:	Rectified	Color Body:	Glazed
Recycled Content:	None	Surface Type:	Matte & Polished
		Recommended Grout Joint:	TCNA recommendations for rectified product based on site conditions

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	≤0.5%	Chemical Resistance:	CLASS A
Shade Variation (1, 2, 3, 4)	2	Dynamic COF:	POLISHED ≥ 0.42 DRY / HONED ≥ 0.50 WET
Scratch Hardness (MOHS)	5	Breaking Strength:	≥360
Frost Resistant:	Yes	Thermal Shock Resistance:	
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm ² :	

OF FACES / SIZES

	24X48	32X32	24X24	12X24
CARRARA GIOIA	30	30	54	60
STATUARIETTO	30	36	54	60
ARABESCATO	30	30	54	60
CALACATTA	30	30	54	60
STATUARIO NUOVO	23	30	54	60
NERO VENATO	20	20	36	40
PARADISO ARGENTO	20	18	36	40
ONYX NUVOLATO	30	24	54	60
TRAVERTINO INSTRATA	12			56

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacture. Use constitutes acceptance.