

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME

**ANCIENT**

## TECHNICAL CHARACTERISTICS

Available Formats:	6X6		
Style Description:		Glaze Application Method:	INKJET
Thickness in mm:	8.5	Number of Faces/Screens:	24
Modular Suitability:	NO	Number of Punches/Molds:	
Application:	RESIDENTIAL, WALL, EXTERIOR	Body Type:	PORCELAIN
Rectified or Pressed:	PRESSED	Color Body:	GLAZED
Recycled Content: Post or Pre Customer		Surface Type:	SATIN
		Recommended Grout Joint:	2MM

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	.16%	Chemical Resistance:	GL / GLA
Shade Variation (1, 2, 3, 4)		Dynamic COF:	0.39
Scratch Hardness (MOHS)	7	Breaking Strength:	>1504 N
Frost Resistant:		Thermal Shock Resistance:	
PEI/Abrasion Resistance:	3	Deep Abrasion Test <175mm <sup>2</sup> :	YES

*ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacture. Use constitutes acceptance.*