

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

TUSCANY

TECHNICAL CHARACTERISTICS

Available Formats:	18X18, 12x12, 13x22		
Style Description:	STONE LOOK	Glaze Application Method:	Standard Screen
Thickness in mm:	7.4 for 12 x12 & 13x22 7.2 for 18x18	Number of Faces/Screens:	6
Modular Suitability:	NO	Number of Punches/Molds:	N/A
Application:	RESIDENTIAL	Body Type:	CERAMIC
Rectified or Pressed:	PRESSED	Color Body:	GLAZED
Recycled Content: Post or Pre Customer	NO	Surface Type:	SATIN
		Recommended Grout Joint:	5mm

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	6% - 10%	Chemical Resistance:	≥ TO CLASS GB
Shade Variation (1, 2, 3, 4)	3	Dynamic COF:	>0.42
Scratch Hardness (MOHS)	RESISTANT	Breaking Strength:	≥TO 500 N (THICKNESS LOWER 7.5MM)
Frost Resistant:	NO	Thermal Shock Resistance:	NO
PEI/Abrasion Resistance:	4	Deep Abrasion Test <175mm ² :	NO

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacture. Use constitutes acceptance.