

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

GRAFFITI

TECHNICAL CHARACTERISTICS

Available Formats:	2x18		
Style Description:	PORCELAIN BRICK	Glaze Application Method:	Inkjet
Thickness in mm:	9.5mm	Number of Faces/Screens:	70, Nolita has 24
Application:	WALL/FLOOR/EXTERIOR POOL/FIREPLACE	Number of Punches/Molds:	70, Nolita has 24
Rectified or Pressed:	Pressed Edge	Body Type:	Porcelain
Recycled Content: Post or Pre Customer		Surface Type:	Undulated
		Recommended Grout Joint:	3mm

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	< 0.5%	Chemical Resistance:	HA / LA
Shade Variation (1, 2, 3, 4)	V2, V3 for Nolita Colors	Dynamic COF:	> 0.42
Frost Resistant:	YES	Breaking Strength:	≥ 700N
PEI/Abrasion Resistance:	4, 5 for Nolita Sand, Nolita Pearl & Graffiti White	Thermal Shock Resistance:	OK

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacture. Use constitutes acceptance.