

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

SHOWTIME

TECHNICAL CHARACTERISTICS

Available Formats:	13.25x10.25		
Style Description:	Decorative Stone	Glaze Application Method:	
Thickness in mm:	8mm	Number of Faces/Screens:	
Application:	Residential Walls & Floors. Residential Walls Only for Metal Inlay	Number of Punches/Molds:	
Rectified or Pressed:		Body Type:	Marble Stone
Recycled Content: Post or Pre Customer		Surface Type:	Flat
Visual Characteristics:	Cascade Waterjet	Recommended Grout Joint:	Non-Sanded grout should be used with the showtime with metal material.

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:		Chemical Resistance:	
Shade Variation (1, 2, 3, 4)		Dynamic COF:	
Frost Resistant:		Breaking Strength:	
PEI/Abrasion Resistance:		Thermal Shock Resistance:	

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacture. Use constitutes acceptance.