

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

CORA

TECHNICAL CHARACTERISTICS

Available Formats:	12x24 & 24x24, 24x48*		
Style Description:	Marble	Glaze Application Method:	Inkjet
Thickness in mm:	12x24=7mm / 24x24=8.5mm	Number of Faces/Screens:	13
Modular Suitability:		Number of Punches/Molds:	1
Application:	Residential	Body Type:	Porcelain
Rectified or Pressed:	Pressed (*24x48 Rectified)	Color Body:	
Recycled Content: Post or Pre Customer	N/A	Surface Type:	Matte
		Recommended Grout Joint:	3 mm

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	12x24=0.25 24x24=0.2	Chemical Resistance:	12x24=HA-A-LA 24x24=HA-LA-A
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	>0.69
Scratch Hardness (MOHS)	8	Breaking Strength:	12x24=1300 N 24x24=1879 N
Frost Resistant:	Yes	Thermal Shock Resistance:	150°C
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm ² :	No

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacture. Use constitutes acceptance.