

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

KALKAREA

TECHNICAL CHARACTERISTICS

Available Formats:	12x24 & 24x48		
Style Description:	Limestone look, anti slip finish	Glaze Application Method:	Inkjet
Thickness in mm:	9	Number of Faces/Screens:	96
Modular Suitability:	Yes	Number of Punches/Molds:	8
Application:	Residential, Commercial, Exterior	Body Type:	Porcelain
Rectified or Pressed:	Rectified	Color Body:	
Recycled Content: Post or Pre Customer	0%	Surface Type:	Matte, Textured
		Recommended Grout Joint:	1/16"

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	(= 0,5%) --> 0,1%	Chemical Resistance:	Resistant
Shade Variation (1, 2, 3, 4)	2	Dynamic COF:	(>42) --> 0,8
Scratch Hardness (MOHS)	N/A	Breaking Strength:	(>1300) --> 2751
Frost Resistant:	Yes	Thermal Shock Resistance:	Resistant
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm ² :	Yes

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacture. Use constitutes acceptance.