

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME

**OYSTER**

## TECHNICAL CHARACTERISTICS

Available Formats:	12x24, 24x48, Mosaic		
Style Description:	Glazed Porcelain Tile	Glaze Application Method:	Inkjet
Thickness in mm:	9.5	Number of Faces/Screens:	NO.16 FOR 24"X48" - NO.64 FOR 12"X24"
Modular Suitability:	Yes	Number of Punches/Molds:	1
Application:	Residential, Commercial	Body Type:	Porcelain
Rectified or Pressed:	Rectified	Color Body:	Glazed
Recycled Content: Post or Pre Customer	10%	Surface Type:	Matte
		Recommended Grout Joint:	

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	$\leq 0,1\%$	Chemical Resistance:	A - LA -HA
Shade Variation (1, 2, 3, 4)	2	Dynamic COF:	wet > 0,42
Scratch Hardness (MOHS)	$\geq 6$	Breaking Strength:	$S \geq 1300N$ / $R \geq 35 N/mm^2$
Frost Resistant:	Yes	Thermal Shock Resistance:	Resistant
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm <sup>2</sup> :	No

*ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacture. Use constitutes acceptance.*