

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

Solida

TECHNICAL CHARACTERISTICS

Available Formats:	12x24, 24x24		
Style Description:	Concrete	Glaze Application Method:	Inkjet
Thickness in mm:	12x24=7mm 24x24=8.5mm	Number of Faces/Screens:	12x24=20 24x24=10
Modular Suitability:	No	Number of Punches/Molds:	1
Application:	Residential	Body Type:	Porcelain
Rectified or Pressed:	Pressed	Color Body:	
Recycled Content: Post or Pre Customer	N/A	Surface Type:	Matte Textured
		Recommended Grout Joint:	3 mm

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	12x24=.016 24x24=0.18	Chemical Resistance:	HA-A-LA
Shade Variation (1, 2, 3, 4)	2	Dynamic COF:	0.69
Scratch Hardness (MOHS)	8	Breaking Strength:	12x24=1375 N 24x24=1805 N
Frost Resistant:	Yes	Thermal Shock Resistance:	150°F (+)
PEI/Abrasion Resistance:	IV (silver PEI III)	Deep Abrasion Test <175mm ² :	No

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacture. Use constitutes acceptance.