

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

Cremo Marfil

TECHNICAL CHARACTERISTICS

Available Formats:	12x24, 24x24, 24x48, 3" Hex, bullnose		
Style Description:		Glaze Application Method:	Inkjet
Thickness in mm:	12x24=7mm/24x24=8.5mm	Number of Faces/Screens:	12x24=9 / 24x24=5
Modular Suitability:	No	Number of Punches/Molds:	1
Application:	Residential	Body Type:	Porcelain
Rectified or Pressed:	Pressed	Color Body:	
Recycled Content: Post or Pre Customer	N/A	Surface Type:	Matte
		Recommended Grout Joint:	3 mm

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	0.13	Chemical Resistance:	Yes
Shade Variation (1, 2, 3, 4)	2	Dynamic COF:	0.74
Scratch Hardness (MOHS)	8	Breaking Strength:	12x24=1375N/24x24=1805N
Frost Resistant:	Yes	Thermal Shock Resistance:	150°C (+)
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm ² :	NO

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacture. Use constitutes acceptance.