

NEW PRODUCT SERIES

Technical Information Spec-sheet



INTERNATIONAL WHOLESALE TILE, LLC

SERIES NAME

Foresta

TECHNICAL CHARACTERISTICS

Available Formats:	6x36		
Style Description:	Wood look	Glaze Application Method:	Inkjet
Thickness in mm:	8mm	Number of Faces/Screens:	10
Modular Suitability:	No	Number of Punches/Molds:	1
Application:	Residential <ul style="list-style-type: none"> • Wall wet/dry • Floor wet/dry • Hearth • Exterior wall • Exterior floor (matte) Light Commercial <ul style="list-style-type: none"> • Wall wet/dry • Hearth • Floor dry (matte) • Exterior wall 	Body Type:	Porcelain
Rectified or Pressed:	Pressed	Color Body:	No
Recycled Content: Post or Pre Customer	N/A	Surface Type:	Matte
Country of Origin	Turkey	Recommended Grout Joint:	3mm

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	.19%	Chemical Resistance:	HA-A-LA
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	0.69
Scratch Hardness (MOHS)	8	Breaking Strength:	1648N
Frost Resistant:	Yes	Thermal Shock Resistance:	150° C
PEI/Abrasion Resistance:	4	Deep Abrasion Test <175mm ² :	No

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacture. Use constitutes acceptance.